

COMMERCIAL GREENHOUSES

VENLO AND OPEN-ROOF STYLE

Space-efficient mass production



Open Roof, Young's Plant Farm, AL



Venlo, Mucci Farms, Kingsville, Ontario



Roof washing equipment on Venlo

VENLO AND OPEN-ROOF STYLE GREENHOUSES

The **Venlo** greenhouse is a great choice for large commercial operations, offering optimal light transmittance and exceptional ventilation. It features a high light transmitting tempered-glass roof and a truss design that accommodates energy/shade curtains, growing systems, and more. Alternating skip vents allow for the release of heat and humidity at a controlled pace.

The **Open-Roof** greenhouse provides a protected environment with easy outdoor access for crop conditioning and steering. It has excellent ventilation and can accommodate multiple glazing types. Its unique roof design features full vertical vents that pivot at the gutter sides for 86° natural ventilation with the roof fully open, or partial roof opening during bad weather. The peak gutter keeps unwanted moisture off the crops.

Get to Know the Venlo and Open-Roof

- ✓ Single-piece factory-welded energy trusses
- ✓ Insulated aluminum gutters suitable for roof washing equipment and chalk machines
- ✓ Optional: powder-coated frame, flashings, and extrusions
- ✓ Optional: direct and indirect drive roof vents
- ✓ Optional: insect screen roof vents (Venlo only)

Optimal Growing Conditions

- **Amplifies natural light**
The tempered-glass exterior minimizes light loss, while allowing for higher light transmission.
- **Delivers optimal ventilation and airflow**
Higher ceilings and shallow peak heights offer greater floor-to-vent room for increased air volume, improved airflow, and a healthier growing environment. Houses can be actively or passively ventilated.
- **Minimizes moisture**
Condensation channeling to the gutters negates drip damage to crops.
- **Provides heat protection**
High sidewalls provide a natural heat buffer for the crop and increase production space. Shade curtains retain heat in winter and protect crops from the summer sun.

Stands the Test of Time

- **Durable weather protection**
Stands up to heavy snow, wind, and crop loads.
- **Reduces maintenance**
Tempered glass minimizes reglazing and upkeep.
- **Lasts for generations**
Hot-dipped galvanized North American steel profiles for strength and longevity.



VENLO SPECIFICATIONS

- Standard widths: 8 and 12 meters (26.24' and 39.36')
- Standard gutter height: 7.3m (24')
- Standard bay spacing: 4m (13.12')
- Load rating: up to 30# roof
- Non-standard sizes available upon request

OPEN ROOF SPECIFICATIONS

- Standard Open-Roof Width: 3 peak 12 meter (39.36') or 36'
- Standard gutter height: 7.3m (24')
- Standard bay spacing: 4m (13.12')
- Load rating: up to 30# roof
- Non-standard sizes available upon request

PROSPIANT

EXPERTISE YOU CAN TRUST. CAPABILITIES YOU CAN COUNT ON.

Proven Track Record of Success

- 10,000+ customers
- 3,000+ completed projects

Qualified In-House Talent

- Comprehensive engineering, including structural and MEP
- Experienced OSHA 10/30 certified project managers
- Extensive installer network
- Licensed in 50 states and Canada (engineering and general contracting)

North American Manufacturing

- U.S. and Canada
- NGMA member

Contact us to purchase

(513) 242-0310

sales@prospiant.com

www.prospiant.com



©2023 Prospiant. All rights reserved.